

- 2. 2nd SUFFIX,"X" INDICATES CRACKING PRESSURE CRACKING PRESSURE ± 15% OF NOMINAL, RESEAT WITHIN 20% OF NOMINAL
 CRACKING PRESSURE.
 SEE SHEET 2 FOR AVAILABLE PRESSURE RANGES.
- 3. 3rd SUFFIX INDICATES NUT OPTION NO SUFFIX NUT INCLUDED LN LESS NUT
- 4. CRITICAL DIMENSIONS ARE CIRCLED AND SUBJECT TO INSPECTION.
- 5. DIMENSIONS IN PARENTHESES ARE FOR REFERENCE ONLY.
- 6. ALL DIMENSIONS ARE IN INCHES, WITH NOMINAL DIMENSION IN METRIC BELOW.
- 7. TEMPERATURE RANGE: -65°F TO 180°F.
- 8. WEIGHT 0.25 OZ. (7 GRAMS).
- 9. MATERIAL DFARS 252.225.7009, OR 252.225.7014, COMPLIANT.
- 10. MATERIAL ROHS COMPLIANT.

	DRAWN BY	DMC	_	04/06/20		D ®	Halkey-Roberts®			
	APPROVED BY		DATE			$IR^{\scriptscriptstyle{\circledR}}$	наіке	y-Kop	erts	
	MATERIAL				TITLE					_
RIA	FINISH					RELIE	F VALVI	E, PRESS	URE	
	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES		THIRD ANGLE PR	THIRD ANGLE PROJECTION		DRAWING N	0.	DWW	REV	
PERTY							~C750R	YXXX	B	

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS SOLE PROPERTY
OF HALKEY-ROBERTS CORPORATION ST. PETERSBURG, FL. ANY
REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN
PERMISSION OF HALKEY-ROBERTS CORPORATION IS PROHIBITED.

GATES, PARTING LINES, AND FLASH PER QUALITY CRITERI

INLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
OLERANCES:
ANGULAR: ±1°
TWO PLACE DECIMAL ±.01
THREE PLACE DECIMAL ±.005

A C750RPXXX

SCALE
1:1 DO NOT SCALE DRAWING SHEET

1 OF 2

DRAWING NO. **REVISION HISTORY Customer Drawing** C750RPXXX В DESCRIPTION (ECO) DATE **APPROVED** 04/06/20 Α ΑK NEW DRAWING REPLACES C750RPXX ECO 10435 В 04/17/20 ADD LN SUFFIX OPTION TO SHEET 2. ECO 10461 ΑK

NUT

FINISH

BLACK

BLACK

BLACK

CRACK

(PSI)

1.0

2.0 3.0

PRESSURE

SUFFIX

750RPNP10

BODY

FINISH

750RPNP025 NICKEL PLATED NICKEL PLATED

NICKEL PLATED NICKEL PLATED

NUT

FINISH

CRACK

PRESSURE

(PSI)

0.25

1.0

SUFFIX

750RPBK10

750RPBK20

750RPBK30

BODY

FINISH

BLACK

BLACK

BLACK

SUFFIX	BODY FINISH	NUT FINISH	CRACK PRESSURE (PSI)
750RP01 750RP02 750RP04 750RP05 750RP06 750RP065 750RP07 750RP07LN 750RP10 750RP12 750RP12 750RP12 750RP20 750RP23 750RP25 750RP25 750RP30 750RP35 750RP40 750RP50 750RP60 750RP65 750RP70 750RP75 750RP100 750RP150 750RP150 750RP150 750RP100	CLEAR	BLACK	0.1 0.2 0.4 0.5 0.6 0.65 0.7 1.0 1.12 1.2 1.5 2.0 2.3 2.5 3.0 3.5 4.0 5.0 6.0 6.5 7.0 7.5 10.0 15.0 20.0

	DRAWN BY	DMC	DATE 04/06/20	///	3 Hallian Dalameta	
	APPROVED BY		DATE]47,	ង្គ Halkey-Roberts	
	MATERIAL			TITLE	<u> </u>	
MOLDED PARTS: GATES, PARTING LINES, AND FLASH PER QUALITY CRITERIA	FINISH				RELIEF VALVE, PRESSURE	
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS SOLE PROPERTY	UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: 1° TWO PLACE DECIMAL ±.01 THREE PLACE DECIMAL ±.005		THIRD ANGLE PROJECTION	SIZE	C750RPXXX	B
OF HALKEY-ROBERTS CORPORATION ST. PETERSBURG, FL. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF HALKEY-ROBERTS CORPORATION IS PROHIBITED.				SCALE 1:1	DO NOT SCALE DRAWING SHEET 2 OF 2	2